

# TSP7EC

## MOBILE GRANDSTAND

### Quick Guide

#### Setup

- Extend tongue jack ① and disconnect tow vehicle.
- Stow safety chains, 12V connector, emergency breakaway cable. Caution - Do not remove breakaway pin from switchbox.
- Level bleacher lengthwise using tongue jack (adjust to ground slope)
- Rotate front corner leveling/support jacks ② to vertical, re-pin, extend jack legs to ground.
- Unpin canopy transport lock bar. ③
- Extend and re-pin canopy transport lock bar. ③
- Remove canopy support lock pin. ④
- Repeat ③ ④ at opposite canopy end.
- Tighten winches ⑤ to open canopy 1ft - 2ft.
- Rotate all remaining leveling/support jacks ② to vertical, re-pin, extend jack legs to ground.
- Tighten winches ⑤ until canopy supports are straight, insert lock pins. ④
- Remove stairs and handrails from storage locations. ⑥
- Retract tongue jack ①
- **Remove hitch/transport lock-pin. ⑦**
- Open lid on mechanical compartment. ⑧  
Rotate timer switch to **"ON"** position.  
Remove control from compartment.
- Visually check that area is clear.
- Push **"OPEN"** button until grandstand is fully extended.
- Install stairs and handrails at ends of walkway ⑩.
- Unpin and remove aisle handrails ⑨ from storage positions and insert into aisleway.
- Check leveling/support jacks ② and reset as required.
- Rotate timer switch to **"OFF"** position.
- Stow control pendant, close compartment lid and secure. ⑧



#### Close

- **Remove aisle handrails, ⑨** return to storage positions and secure.
- Remove stairs and rails at walkway ends ⑩
- Open lid on mechanical compartment. ⑧  
Rotate timer switch to **"ON"** position.  
Remove control from compartment.
- Visually check that area is clear.
- Press and hold **"CLOSE"** button until grandstand is fully closed.
- **Install hitch/transport lock-pin. ⑦**
- Rotate timer switch to **"OFF"** position. Store control pendant. ⑧ Close compartment lid.
- Store stairs and handrails ⑥ and secure.
- Remove pins from canopy support columns at each end. ④ Place in storage holes.
- Loosen winches at each end (alternating ends) until canopy is 1ft - 2ft from closed. ⑤
- Retract, rotate, and repin all frame support jacks except front corner jacks. ②
- Loosen winches ⑤ until canopy is closed.
- Repin canopy transport lock bar ③ at each end.
- Extend tongue jack leg to ground contact. ①
- Retract, rotate, and repin front corner jacks. ②
- Connect tow vehicle - coupler, safety chains, 12V connector, emergency breakaway cable.
- Check coupler, signal lights and brake operation prior to towing.

Read and understand operation guide prior to bleacher towing and operation.